



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ALPHA OM350/OM325H/OM325F SAC 305

MANUFACTURER'S NAME: ALPHA METALS, INC
ADDRESS: 600 ROUTE 440
JERSEY CITY, NJ 07304

TRANSPORT EMERGENCY #: CHEMTREC: 1-800-424-9300

BUSINESS PHONE: 1-201-434-6778

2. INGREDIENT AND EXPOSURE LIMIT INFORMATION

CHEMICAL NAME	CAS #	% W/W	OSHA PEL - TWA
TIN	7440-31-5	80 - 85	2.0 mg/m3
SILVER	7440-22-4	1 - 5	0.01 mg/m3
COPPER	7440-50-8	0.2 - 1	0.2 mg/m3
MODIFIED ROSIN	Proprietary	1 - 5	**
DIETHYLENE GLYCOL DIBUTYL ETHER	112-73-2	2 - 5	NE
POLYMER	9003-28-5	0.2 - 1.5	NE
ROSIN	65997-06-0	1 - 5	**

**SENSITIZER

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: MODERATE EYE IRRITANT.
WILL NOT BURN
TOXIC BY INHALATION.
MODERATE GASTROINTESTINAL TRACT IRRITANT.
MODERATE RESPIRATORY TRACT IRRITANT.
CAUSES SKIN IRRITATION

HMIS RATING SYSTEM:
Health: 1 ; Flammability: 0 ; Reactivity: 0 ; Protection: C

NFPA RATING SYSTEM:
Health: 2 ; Flammability: 0 ; Reactivity: 0

ROUTES OF ENTRY: INHALATION; INGESTION; SKIN CONTACT; EYE CONTACT;
ABSORPTION;

TARGET ORGANS: BLOOD; DIGESTIVE TRACT; KIDNEYS; NERVOUS SYSTEM; EYES;
SKIN.

MEDICAL CONDITIONS AGGRAVATED: DIGESTIVE TRACT DISEASE; KIDNEY DISEASE
EYE DISEASE. SKIN DISEASE INCLUDING ECZEMA
AND SENSITIZATION.

IMMEDIATE (ACUTE) SYMPTOMS OVER-EXPOSURE BY ROUTE OF EXPOSURE:
INHALATION: CAN CAUSE MODERATE RESPIRATORY IRRITATION, DIZZINESS,
WEAKNESS, FATIGUE, NAUSEA AND HEADACHE. MAY CAUSE AN



MATERIAL SAFETY DATA SHEET

3. HAZARDS IDENTIFICATION (Cont.)

ALLERGIC REACTION. MAY CAUSE RESPIRATORY TRACT SENSITIZATION, CHARACTERIZED BY ASTHMA-LIKE SYMPTOMS.

EYES: CAN CAUSE MODERATE IRRITATION, TEARING AND REDDENING, BUT NOT LIKELY TO PERMANENTLY INJURE EYE TISSUE.

SKIN CONTACT: CAN CAUSE SLIGHT IRRITATION.

INGESTION: IRRITATING TO MOUTH, THROAT, AND STOMACH. CAN CAUSE ABDOMINAL DISCOMFORT, NAUSEA, VOMITING AND DIARRHEA.

LONG TERM (CHRONIC) HEALTH EFFECTS:

CARCINOGENICITY: NONE OF THE SUBSTANCES HAVE BEEN SHOWN TO CAUSE CANCER IN LONG TERM ANIMAL STUDIES. NOT A CARCINOGEN ACCORDING TO NTP, IARC, OR OSHA.

REPRODUCTION: NO DATA AVAILABLE TO INDICATE PRODUCT OR ANY COMPONENTS PRESENT AT GREATER THAN 0.1% MAY CAUSE BIRTH DEFECTS.

MUTAGENICITY: NO DATA AVAILABLE TO INDICATE PRODUCT OR ANY COMPONENTS PRESENT AT GREATER THAN 0.1% IS MUTAGENIC OR GENOTOXIC.

4. FIRST AID MEASURES

SKIN EXPOSURE: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRY. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

EYE EXPOSURE: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 20 MINUTES RETRACTING EYELIDS OFTEN. TILT THE HEAD TO PREVENT CHEMICAL FROM TRANSFERRING TO THE UNCONTAMINATED EYE. GET IMMEDIATE MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, HAVE A TRAINED INDIVIDUAL ADMINISTER OXYGEN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION AND HAVE A TRAINED INDIVIDUAL ADMINISTER OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: SEEK MEDICAL ATTENTION IMMEDIATELY.

NOTES TO DOCTOR: NO ADDITIONAL FIRST AID INFORMATION AVAILABLE

5. FIRE FIGHTING MEASURES

FLAMMABILITY SUMMARY: NOT COMBUSTIBLE

FLASH POINT: N/A

AUTOIGNITION TEMPERATURE: N/E

EXPLOSIVE LIMITS % IN AIR: N/E

EXTINGUISHING MEDIA: USE ALCOHOL RESISTANT FOAM, CARBON DIOXIDE, OR DRY CHEMICAL WHEN FIGHTING FIRES. WATER OR FOAM MAY CAUSE FROTHING IF LIQUID IS BURNING BUT IT STILL MAY BE USEFUL EXTINGUISHING AGENT IF CAREFULLY APPLIED TO THE SURFACE OF THE FIRE. DO NOT DIRECT A STREAM OF WATER INTO



MATERIAL SAFETY DATA SHEET

5. FIRE FIGHTING MEASURES (Cont.)

FIRE AND EXPLOSION METHODS: MOLTEN MATERIAL.
MATERIAL MAY BE IGNITED ONLY IF PREHEATED TO
TEMPETURES ABOVE THE HIGH FLASH POINT, FOR
EXAMPLE IN A FIRE. DUST AT SUFFICIENT
CONCENTRATIONS CAN FORM EXPLOSIVE MIXTURES
WITH AIR.

FIRE FIGHTING METHODS: WILL NOT BURN, NO SPECIAL INSTRUCTIONS
AVAILABLE. USE METHODS APPROPRIATE FOR
SURROUNDING MATERIALS.

HAZARDOUS COMBUSTION PRODUCTS: CARBON MONOXIDE; CARBON DIOXIDE; METAL FUMES;
TOXIC FUMES.

6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS AND EQUIPMENT: EXPOSURE TO THE SPILLED MATERIAL MAY BE IRRITATING
OR HARMFUL. FOLLOW PERSONAL PROTECTIVE EQUIPMENT
RECOMMENDATIONS FOUND IN SECTION VIII OF THIS
MSDS.

METHODS FOR CLEAN-UP: WEAR COMPLETE AND PROPER PERSONAL PROTECTIVE
EQUIPMENT FOLLOWING THE RECOMMENDATION OF SECTION
VIII GATHER AND STORE IN A SEALED CONTAINER
PENDING A WASTE DISPOSAL EVALUATION. DO NOT USE
BROOM OR AIR CLEANING ETC.

7. HANDLING AND STORAGE

HANDLING MEASURES: HARMFUL OR IRRITATING MATERIAL. AVOID CONTACTING AND AVOID
BREATHING THE MATERIAL. USE ONLY IN A WELL VENTILATED
AREA.
AS WITH ALL CHEMICALS, GOOD INDUSTRIAL HYGIENE PRACTICES
SHOULD BE FOLLOWED WHEN HANDLING THIS MATERIAL. AVOID
CONTACT WITH MATERIAL, AVOID BREATHING DUSTS OR FUMES, USE
ONLY IN A WELL VENTILATED AREA. WASH THOROUGHLY AFTER
HANDLING; WASH HANDS BEFORE EATING; DO NOT GET IN EYES,
ON SKIN AND CLOTHING; MINIMIZE DUST GENERATION AND
ACCUMULATION; AVOID CREATING DUSTS AS AN EXPLOSIVE
HIGH CONCENTRATIONS.

STORAGE MEASURES: NO SPECIAL REQUIREMENTS
KEEP AWAY FROM FOOD AND DRINKING WATER. STORE IN A COOL
DRY PLACE.



MATERIAL SAFETY DATA SHEET

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING MEASURES: USE LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO MINIMIZE EXPOSURES AND MAINTAIN OPERATOR COMFORT.
ENGINEERING CONTROLS MUST BE DESIGNED TO MEET THE OSHA CHEMICAL SPECIFIC STANDARD IN 29 CFR 1910. VENTILATION IS REQUIRED TO MAINTAIN OPERATOR EXPOSURE BELOW PUBLISHED EXPOSURE LIMITS. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS; EXPLOSION PROOF EXHAUST VENTILATION SHOULD BE USED. FACILITIES STORING OR USING THIS MATERIAL SHOULD BE EQUIPPED WITH AN EYEWASH AND SAFETY SHOWER.

RESPIRATORY PROTECTION: RESPIRATORY PROTECTION MAY BE REQUIRED TO AVOID OVEREXPOSURE WHEN HANDLING THIS PRODUCT. GENERAL OR LOCAL EXHAUST VENTILATION IS THE PREFERRED MEANS OF PROTECTION. USE A RESPIRATOR IF GENERAL ROOM VENTILATION IS NOT AVAILABLE OR SUFFICIENT TO ELIMINATE SYMPTOMS.
FOLLOW A RESPIRATORY PROTECTION PROGRAM THAT MEETS 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS WHENEVER WORK PLACE CONDITIONS WARRANT THE USE OF A RESPIRATOR. WEAR A NIOSH APPROVED RESPIRATOR IF ANY EXPOSURE IS POSSIBLE.

EYE PROTECTION: WEAR CHEMICALLY RESISTANT SAFETY GLASSES WITH SIDE SHIELDS WHEN HANDLING THIS PRODUCT. DO NOT WEAR CONTACT LENSES.

SKIN PROTECTION: WEAR GOGGLES AND A FACE SHIELD
WEAR PROTECTIVE GLOVES. INSPECT GLOVES FOR CHEMICAL BREAK-THROUGH AND REPLACE AT REGULAR INTERVALS. CLEAN PROTECTIVE EQUIPMENT REGULARLY. WASH HANDS AND OTHER EXPOSED AREAS WITH MILD SOAP AND WATER BEFORE EATING, DRINKING, AND WHEN LEAVING WORK

CONTROL PARAMETERS:	-----ACGIH EXPOSURE LIMITS-----		
CHEMICAL NAME	TLV-TWA	STEL	CEILING
ROSINS	sensitizer;keep exposure as low as possible		
TIN	2 mg/m3 TWA		
SILVER	0.1 mg/m3 TWA		
COPPER	0.2 mg/m3 TWA		



Cookson Electronics

A Division of Cookson Group plc

Page 5 of 6
Revised 3/28/06
Replaces 3/28/06
Printed 3/28/06
MSDS ID: AA 00149817

Alpha Metals
600 Route 440
Jersey City, New Jersey 07304
(201) 434-6778
(201) 434-7508 fax
www.alphametals.com

MATERIAL SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

COLOR: GREY
ODOR: NONE
pH: N/A

10. STABILITY AND REACTIVITY

DECOMPOSITION PRODUCTS: METAL FUMES; TOXIC FUMES.
INCOMPATIBLE MATERIALS: STRONG ACIDS; STRONG OXIDIZING AGENTS;
CONDITIONS TO AVOID: NONE KNOWN
CONTAMINATION: CONTACT WITH AIR. CONTACT WITH WATER

11. TOXICOLOGICAL INFORMATION

COMPONENT TOXICOLOGY DATA (NIOSH)
CHEMICAL NAME LD50/LC50
DIETHYLENE GLYCOL DIBUTYL ETHER Oral LD50 Rat: 3900 mg/Kg
POLYMER Oral LD50 Rat: 20 g/Kg

12. ECOLOGICAL INFORMATION

OVERVIEW: SLIGHT ECOLOGICAL HAZARD. IN HIGH CONCENTRATIONS, THIS PRODUCT MAY BE DANGEROUS TO PLANTS AND/OR WILDLIFE.

13. DISPOSAL CONSIDERATIONS

WASTE DESCRIPTION: SPENT OR DISCARDED MATERIAL IS PROBABLY A HAZARDOUS WASTE.
DISPOSAL METHODS: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, LOCAL, OR PROVINCIAL LAWS AND REGULATIONS.

14. TRANSPORT INFORMATION

SHIPPING BASIC DESCRIPTION: DOT & IATA: NOT RESTRICTED



Cookson Electronics

A Division of Cookson Group plc

Page 6 of 6
Revised 3/28/06
Replaces 3/28/06
Printed 3/28/06
MSDS ID: AA 00149817

Alpha Metals
600 Route 440
Jersey City, New Jersey 07304
(201) 434-6778
(201) 434-7508 fax
www.alphametals.com

MATERIAL SAFETY DATA SHEET

15. REGULATORY INFORMATION

TSCA STATUS: ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY
OF EXISTING CHEMICAL SUBSTANCES.

REGULATED CHEMICALS:

CHEMICAL NAME		REGULATION
SILVER	7440-22-4	SARA 313

CALIFORNIA SCAQMD RULE 443.1 VOCS:

16. OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed of implied regarding the accuracy of these data or the results to be obtained from the use thereof. Additionally, Alpha Metals, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.